

Canon



CORPORATE SOLUTIONS



Color
imagerUNNER®
C 2 5 5 0

meap
POWERED BY I

SPECIFICATIONS



MAIN UNIT		Installation Space (W x D): 34" x 29-3/4" (when the Stack Bypass is extended)		Communication Protocol	
Type:	Color Digital Multifunction Imaging System	Weight:	Approximately 256 lb. (116kg Main Unit) Approximately 275 lb. (125kg with DADF)	File:	FTP (TCP/IP), SMB (TCP/IP), NCP (IPX), WebDAV
Copying Method:	Laser Dry Electrostatic Transfer	Power Requirements:	120V AC, 60Hz, 15A	E-mail/I-fax:	SMTP, POP3, I-fax (Simple, Full)
Developing System:	Dry Dual Component Developing System	Power Consumption:	1,500W	Data Format	
Memory:	Standard 1GB RAM Maximum 1.5GB RAM	Plug:	NEMA 5-15P	File, E-mail:	TIFF, JPEG, PDF, PDF (Compact),** PDF (Trace & Smooth),** PDF (OCR),** Encrypted PDF,*** Digital Signature PDF (Device,*** User*)
Hard Disk Drive:	80GB	Toner (Estimated Yield):	Black: 26,000 Images @ 5% Coverage Color: 14,000 Images @ 5% Coverage	I-fax:	B/W: TIFF (MH, MR, MMR) Color: TIFF (Profile-C)
Network Interface Connections:	10/100Base-TX (RJ-45)	Copy Features		OPTIONAL ACCESSORIES	
Other Interface:	USB 2.0 (Device), USB 2.0 (Host)	Multiple Copies:	1 to 999	Super G3 Fax Board-W2/Super G3 Multi-Line Fax Board-J2	
First-Copy Time:	8.9 Seconds (Color) 5.9 Seconds (B/W)	Max. Copy Reservation:	10 Jobs	Applicable Line: Public Switched Telephone Network (PSTN)	
Warm-Up Time:	38-Seconds After Powering On	Color Mode:	Auto Color, Full Color, Black, Single Color, Two Colors	Connection Lines: One-Line (Super G3 Fax Board W2), Two-Lines (Super G3 Multi-Line Fax Board-J2)	
Copy/Print Speed (B/W, Color):	25/23 ppm (Letter)	Copy Exposure:	Automatic or Manual (9 Levels)	Sending/Original Size: Statement to 11" x 17"	
Scan Resolution:	600 dpi x 600 dpi	Magnification		Recording/Printing Size: Statement to 11" x 17"	
Copy Resolution:	600 dpi x 600 dpi	Preset Reduction:	25%, 50%, 64%, 73%, 78%	PCL Printer Kit-Q3**	
Engine Resolution:	1200 dpi x 1200 dpi (Optional)*	Preset Enlargement:	121%, 129%, 200%, 400%	CPU: Canon Dual Custom Processor (Shared)	
Halftone:	256 Gradations (Continuous-Tone)	Zoom Mode:	25% - 400% (1% Increments)	Memory: 1GB RAM (Standard) 1.5GB RAM (Maximum) (Shared)	
Paper Sources		Print Features		Hard Disk Drive: 80GB (Shared)	
Standard:	Dual 550-Sheet x 2 Paper Cassettes 50-Sheet Stack Bypass	CPU:	Canon Dual Custom Processor (Shared)	Supported PDL: PCL 5c/6	
Optional:	Dual 550-Sheet x 2 Paper Cassettes 2,700-Sheet Paper Deck	Memory:	1GB RAM (Standard) 1.5GB RAM (Maximum) (Shared)	Optional PDL Support: PostScript 3 Emulation (PS Printer Kit-Q3***)	
Maximum:	4,950 Sheets	Hard Disk Drive:	80GB (Shared)	Print Resolution	
Paper Sizes		Print Resolution		PCL 5c: 600 dpi x 600 dpi 2400 dpi equivalent x 600 dpi	
Cassettes:	12" x 18",** 11" x 17",** Legal, Letter, Letter-R, Statement-R, Executive	UFR II:	600 dpi x 600 dpi 1200 dpi x 1200 dpi (Optional)* 2400 dpi equivalent x 600 dpi	PCL 6: 1200 dpi x 1200 dpi (Optional)* 2400 dpi equivalent x 600 dpi	
Bypass:	12-5/8" x 17-11/16", 12" x 18", 11" x 17", Legal, Letter, Letter-R, Statement, Statement-R, Executive, Irregular size (3-7/8" x 5-9/16" to 12-5/8" x 18"), and Envelopes	Printer Driver		PS3 (Optional): 1200 dpi x 1200 dpi (Optional)* 2400 dpi equivalent x 600 dpi	
Acceptable Paper Weight		UFR II:	Windows® (Windows 2000/XP/Server 2003/Windows Vista®) Citrix MetaFrame Macintosh® (OS 10.2.8 or later)	Printer Drivers	
Cassettes:	17 lb. Bond to 90 lb. Index	XPS:*	Windows Vista	PCL 5c: Windows (Windows 2000/XP/Server 2003/Windows Vista) Citrix MetaFrame	
Bypass:	17 lb. Bond to 110 lb. Index	Mail Box Features		PCL 6: Windows (Windows 2000/XP/Server 2003/Windows Vista) Citrix MetaFrame Macintosh (OS 10.2.8 or later)	
Duplexing:	Standard Automatic Trayless Duplexing (Executive to 12" x 18")	Max. Mail Boxes Supported:	100 User Inboxes, One Memory RX Inbox, 50 Confidential Fax Inboxes	PS3 (Optional): Windows (Windows 2000/XP/Server 2003/Windows Vista) Citrix MetaFrame Macintosh (OS 10.2.8 or later)	
Image Reader:	Color Image Reader-L1 (Standard)	Scan Features		Cassette Feeding Unit-Y3	
Acceptable Originals:	Sheet, Book, 3-Dimensional Objects (Up to 4.4 lb.)	Network TWIN Scan:	Standard	Paper Sizes: 12" x 18", 11" x 17", Legal, Letter, Letter-R, Statement-R, Executive [20 lb. Bond (80 g/m ³)]	
Maximum Original Size:	11" x 17"	Network Scan Utility:	Color Network ScanGear	Paper Drawers Capacity: 550-Sheet x 2 Cassettes [20 lb. Bond (80 g/m ³)]	
Document Feeding Method:	Duplexing Automatic Document Feeder (Optional)	Color Universal Send Features		Dimensions (H x W x D): 9-7/8" x 22-1/4" x 27-5/8"	
Acceptable Originals:	Statement to 11" x 17"	Color Mode:	Auto Color Select (Full Color/Grayscale) Auto Color Select (Full Color, B/W) Full Color, Grayscale, B/W	Weight: Approximately 50.7 lb. (23kg)	
Paper Capacity:	50 Sheets	Address Book Capacity:	Max. 1,800 Destinations (Includes 200 One-Touch Buttons) Max. 5 LDAP Servers	Paper Deck-Z1	
Acceptable Paper Weight of Originals:	Simplex 11 lb. to 32 lb. Bond (42 to 128 g/m ³) Duplex 13 lb. to 32 lb. Bond (50 to 128 g/m ³)	Sending Methods:	E-mail, I-fax, SMB, File Server (FTP, IPX, WebDAV), User Inbox, Super G3 Fax (Optional)	Paper Size: Letter	
Scan Speed:	44 ipm (300 dpi) 28 ipm (600 dpi)	Dimensions (H x W x D): 31-1/8" x 22-1/4" x 29-3/4" (Main Unit) 36" x 22-1/4" x 29-3/4" (with DADF)		Paper Deck Capacity: 2,700 Sheets [20 lb. Bond (80g/m ³)]	
Dimensions (H x W x D):				Dimensions (H x W x D): 18-5/8" x 14-5/8" x 23-1/4"	

Finisher-Z1

Number of Trays:	One Tray
Paper Size	
Standard:	12-5/8" x 17-11/16", 12" x 18", 11" x 17", Legal, Letter, Letter-R, Statement, Statement-R, Envelopes (COM10 No. 10, Monarch, DL, ISO-B5, ISO-C5, Yougata 4, Catalog Glove No.8)
Non-Standard Size:	3-7/8" x 5-9/16" to 12-5/8" x 18"
Paper Weight:	17 lb. Bond to 80 lb. Cover
Paper Capacity Per Tray:	500 Sheets (Letter, Statement, Statement-R) or 2-3/4" in Height
	250 Sheets (11" x 17", Legal, Letter-R) or 1-3/8" in Height
Paper Capacity of Staple Mode:	
	500 Sheets/30 Sets (Letter) or 2-3/4" in Height
	250 Sheets/30 Sets (11" x 17", Legal, Letter-R) or 1-3/8" in Height
	500 Sheets/30 Sets (Staple Mode with Different Paper Sizes) or 2-3/4" in Height
Max. Stapling Capacity	
Letter:	50 Sheets (17 lb. to 20 lb. Bond) 30 Sheets (20 lb. to 28 lb. Bond) 2 Sheets (32 lb. Bond to 90 lb. Index)
11" x 17", Legal, Letter-R:	30 Sheets (17 lb. to 20 lb. Bond) 20 Sheets (20 lb. to 28 lb. Bond) 2 Sheets (32 lb. Bond to 90 lb. Index)
Staple Mode:	Corner (11" x 17", Legal, Letter, Letter-R)
	Double (11" x 17", Letter)
Dimensions (H x W x D):	8-1/2" x 27-3/8" x 21-5/8"

Inner 2-Way Tray-D1

Paper Size	
Standard:	12-5/8" x 17-11/16", 12" x 18", 11" x 17", Legal, Letter, Letter-R, Statement, Statement-R, Executive
Non-Standard:	3-7/8" x 5-9/16" to 12-5/8" x 18"
Max. Paper Weight:	17 lb. Bond to 80 lb. Cover
Paper Capacity Per Tray	
Upper Output Tray:	100 Sheets (Letter) 50 Sheets (Other Sizes)
Lower Output Tray:	250 Sheets (Letter) 100 Sheets (Other Sizes)
Dimensions (H x W x D):	6" x 7" x 21-1/2"

OTHER OPTIONAL ACCESSORIES

- Encrypted Secured Print Software-C1*
- Barcode Printing Kit-A1*
- Web Access Software-E1*
- Universal Send PDF Advanced Feature-Set-A1
- Universal Send PDF Security Feature-Set-A1
- Digital User Signature PDF Kit-A1
- Secure Watermark-A1***
- Super G3 Fax Board-W2
- Super G3 Multiline Fax Board-J2
- iR 512MB Expansion RAM-C1
- HDD Data Erase Kit-A1
- HDD Data Encryption Kit-B1
- Voice Guidance Kit-B1°
- Voice Operation Kit-A1°
- Remote Operator's Software Kit-A2
- Platen Cover Type H
- Cabinet-P1
- Copy Tray-J1
- Envelope Feeder Attachment-C2
- FL Cassette-Y1
- FL Cassette-Z1

- Document Tray-J1
- Card Reader-C1
- Card Reader Kit-B1
- Key Switch Unit-A2
- Braille Label Kit-A1
- ADF Access Handle-A1
- Stamp Unit-A1
- eCopy Suite
- imageWARE™ Suite
- Access Management System Kit-A1
- Workflow Composer-B3
- Wireless Network Interface Adapter NB-W1
- 1200 dpi Printer Expansion Board-A1

- * Requires 1200-dpi Printer Expansion Board-A1. If 1200-dpi print is selected, engine speed will slow down.
- ** Not available in top cassette.
- * Check with your Authorized Canon Dealer for availability.
- ** Requires Universal Send PDF Advanced Feature-Set-A1.
- *** Requires Universal Send PDF Security Feature-Set-A1.
- ▲ Requires Digital User Signature Kit-A1.
- ▲▲ Color UFR II Printing is standard.
- ▲▲▲ Requires imageRUNNER 512MB Expansion RAM-C1.
 - Requires PCL Printer Kit-Q3.
 - Requires PS Printer Kit-Q3 if printing PDF files.
 - ° Voice Guidance Kit-B1 and Voice Operation Kit-A1 cannot be installed together.

Canon
image*ANYWARE*

As an ENERGY STAR® Partner, Canon U.S.A., Inc. has determined that this product meets the ENERGY STAR guidelines for energy efficiency. ENERGY STAR and the ENERGY STAR mark are registered U.S. marks. eCopy is a trademark of eCopy, Inc. Windows and Windows Vista are registered trademarks of Microsoft Corporation in the United States and/or other countries. Macintosh is a trademark of Apple Inc. Adobe and PostScript are registered trademarks or trademarks of Adobe Systems Incorporated in the United States and/or other countries. CANON, IMAGERUNNER, MEAP, and the GENUINE logo are registered trademarks of Canon Inc. in the United States and may also be registered trademarks or trademarks in other countries. IMAGEWARE is a registered trademark of Canon U.S.A., Inc. in the United States and is a trademark of Canon Inc. in certain other countries. IMAGEANYWARE is a trademark of Canon. All referenced product names and other marks are trademarks of their respective owners. Specifications and availability subject to change without notice. ©2008 Canon U.S.A., Inc. All rights reserved.

Federal Law prohibits copying of certain documents. Violators may be subject to penalties. We suggest that you check with your own legal counsel. Canon U.S.A., Inc. and Canon Canada, Inc. intend to cooperate with Law Enforcement Agencies in connection with claims of unauthorized copying.



0118W830
0208-C2550-60M-LTM



1-800-OK-CANON
www.usa.canon.com

Canon U.S.A., Inc.
One Canon Plaza
Lake Success, NY 11042